

MIRA Wi-Fi

Full HD Digital Satellite Receiver
With Conax embedded card reader



- One Conax Embedded Smart Card Slot
- High Speed USB 2.0 Connection Support
- External Infra port
- TimeShifting Support
- Built in Wifi
- YouTube Support* (subject to availability)

- RSS Reader & Weather Forecast*
- MKV, AVI, MPG, MP4, TS, VOB, JPEG & MP3 Playback Support
- Software Upgrade via USB
- Dolby Digital Bit-Stream out via HDMI
- Low Power Consumption in Stand-By

* USB Wi-Fi connection required

Features and specifications are subjects to change without notice

MIRA Wi-Fi

Full HD Digital Satellite Receiver
With Conax embedded card reader



TECHNICAL SPECIFICATIONS:

Tuner & Demodulation

Tuner Type: DVB-S / DVB-S2
 Input Connector: F-type, Connector, Female
 Signal Level: -65 to -25 dBm
 LNB Power: Vertical: +13V/+13.5V,
 Horizontal: +18V/+18.5V
 Current: Max. 300mA
 Overload Protection
 22K Tone Frequency: 22±1KHz
 DiSeqC Control: Version 1.0, 1.1, 1.2, USALS
 Demodulation: QPSK, 8PSK
 Input Symbol Rate: 2-45 Mbps,
 1/2, 2/3, 3/4, 5/6, 7/8 and Auto
 FEC:

MPEG TS A/V Decoding

Transport Stream: MPEG-2, MPEG-4 (H.264)
 Input Rate: Max.120Mbit/s
 Aspect Ratio: 4:3, 16:9, Letter Box
 Video Decoding: MPEG-2, MP@ML, MPEG-4 part 10/H264
 Video Resolution: 720*480p/i, 720*576p/i, 1280*720p,
 1920*1080p/i
 Audio Decoding: MPEG-1 layer I/II,
 MPEG-2 layer II, Dolby Digital
 Audio Mode: Left / Right / Stereo/ Mono
 Sampling Rate: 32, 44.1 and 48KHz

System Resources

Main Processor: 600MHz CPU
 Flash Memory: 8 MB
 DDR RAM: 1024 Mbits

A/V & Data Input/Output

IR IN: External IR Connection (Jack Type)
 USB: One USB 2.0 slot Compatible
 HDMI: VER1.4, Type A
 S/PDIF: Coaxial Digital Audio or Dolby Digital Bit Stream
 Output
 SCART: (1-CVBS, 1-L/R,SL,FB),or RCA output

Physical Specifications

Size[W*H*D]: 146mm*111mm*33mm
 Net Weight: 0.25 Kg
 Operation Temperature: 0°C~+45°C
 Storage Temperature: -10°C~+70°C
 Storage Humidity: 5%~95% RH
 (Non-Condensing)



IR RECEIVER INCLUDED